


## Truckies Series PHP15 Electric Belt Drive 300 LPM - Free Air Delivery

**HIGH  
PRESSURE**

### Features & Benefits

- Genuine 3.5HP Motor rating - NOT PEAK HP!
- Certified & registered Pressure Vessel to AS1210
- Manufacturer Data Report available on request
- Smart Start Filters - U.S.A made to reduce start up AMPs by up to 40%
- 2 Stage, Cast Iron Peerless Pump - 5 Year Warranty
- Fully copper wound motor
- 2 Air Outlets! 1 x regulated, 1 x main tank outlet for tank pressure
- Water trap Filter Regulator fitted - auto drain not manual
- A480 Stainless steel inlet & exhaust valves
- Compressed air to AS4637-2006 standard (Free Air Delivery)
- Pallet feet for ease of moving and mounting or Solid rubber puncture proof tyres



**90KG**



PUMP UP TIME TO 100PSI:  
**1.15 - 1.20 MIN**



**1060MM X 450MM X 750MM**



**WARRANTY**  
5 YEAR PUMP / 1 YEAR MOTOR

### Product Descriptions

The PHP15 is a 3.5HP two stage, high pressure compressor capable of running up to 175PSI. Two stage means that the pump has two low pressure heads which then feed into the high pressure head. These machines are fantastic for tyre inflation i.e. truck tyres or applications where large volumes of air at high pressure is required. The advantages of a two stage compressor are that you do not lose volume

of air at higher pressure. The air temperature is some 40% cooler than the standard type of air compressor therefore producing less condensation (moisture).


As a result this is a great compressor for the agricultural sector where there is a requirement to efficiently pump up truck tyres every so often.

### Specifications

CODE	MODEL	CYLINDERS	PUMP DISPLACEMENT	FREE AIR DELIVERY	MAX PSI	MOTOR HP	PUMP TYPE	PUMP RPM	AMPS DRAW	TANK (L)
00100	PHP15	3	15 CFM	300 LPM	175	3.5	2065T	1132	13	55L
00105	PHP15FB	3	15 CFM	300 LPM	175	3.5	2065T	1132	13	110L
00108	PHP15V	3	15 CFM	300 LPM	175	3.5	2065T	1132	13	110L

### High Density Mats

With all stationary tanks it is essential that you have 8-10mm high density rubber mat under the feet to not void warranty, this is also an OH & S requirement.



**CODE**

**DIMENSIONS**

00011

600MM X 200MM

### Air Tools

#### Able to run;

- Low pressure spray gun
- High pressure spray gun
- Car tyre inflation gun
- Truck tyre inflation gun
- Stapling
- Fitting gun
- Framing nail gun
- Grease gun
- Chalking gun
- Riveter gun
- Screw driver
- 1/2" Ratchet gun
- 1/2" Impact gun
- Engine cleaning gun
- Sand blasting gun
- Air hammer
- Hi Torque 1/2" Impact gun

112KG



### PHP15 High Pressure Belt Drive Fat boy 300 LPM - Free Air Delivery

This high pressure compressor has all the performance and standard features as the standard PHP15 but is mounted on a 110 litre horizontal air receiver with pallet feet.

These models are very popular in workshops where there is only single phase power available. Unlike the portable version the 110L Fat Boy tank features a 1/2" tap which is a great feature when you need a lot of air quickly!

Note: this model is also available with a three phase motor ([REFER PAGE 2 - 20](#)).



PUMP UP TIME TO 100PSI:  
**2.30 - 2.35 MIN**



1300MM X 400MM X 840MM

125KG



### PHP15 High Pressure Belt Drive Vertical 300 LPM - Free Air Delivery

This vertical PHP15 compressor is suitable for the home handy man or the mechanic that wants to save space in the shed/workshop. Like other PHP15 models, this will do truck tyre inflation with ease of operation from 150-175PSI and has enough pressure to pop the bead.

With most single phase compressors as you increase the pressure you lose volume of air but not with the two stage pump, you can increase the pressure and maintain the volume of air while limiting AMP draw.



PUMP UP TIME TO 100PSI:  
**2.30 - 2.35 MIN**



610MM X 450MM X 1500MM

### Truck Tyre Inflation

The PHP15 feature the 2065T two stage, high pressure compressor pump capable of running at 175PSI. Two stage means that the pump has two low pressure heads which then feed into the high pressure head. These two stage pumps are fantastic for tyre inflation or applications where large volumes of air at high pressure is required. The advantages of a two stage compressor is that you do not lose volume of air at higher pressure. The air temperature is some 40% cooler than the standard type of air compressor therefore producing less condensation.

*If you plan on using your air compressor to pump up truck tyres the PHP15 model is the perfect choice without needing a huge compressor!*



### Peerless recommended

#### Optional Extras;



- **Electronic auto drain** - Who can remember to drain their tank at the end of each day? Employing an electronic auto drain will remove the build up of condensate in your air receiver also helping with moisture in your air lines. This can be fitted at time of purchase or retro fitted, either with a 10AMP plug or wired into pressure switch.



- **Inline Water Trap** - Running long air lines? We recommend using a water trap every 25M of air line to remove moisture.



- **EHP300 Filter Regulator** - Peerless single phase portable compressors all come with a water trap filter regulator. When purchasing a fatboy or vertical compressor make sure to get this as an extra in order to reduce your air pressure for your air tools.



- **Service Kit** - Maintain your investment! We recommend servicing your air compressor roughly every 2000 working hours, dependant on how hard you are running it. Servicing your air compressor is important like servicing your car to increase it's life span and get the most out of it.