

AFP-Series – ABAC™ Pumps

Honda Petrol

Built in Australia.

Features the world famous ABAC pump and Honda petrol engine with auto idle control. Widely used by the professional in the tyre service trade and agricultural industry, where high pressure may be required.

- ◆ Rated to AS4637.
- ◆ ABAC pump, made in Italy.
- ◆ Cast iron cylinder and crankshaft.
- ◆ Two stage 160psi if required.
- ◆ Intercooler and aftercooler for cool dry air.
- ◆ Honda petrol engine.
- ◆ Oil alert engine shut down.
- ◆ Auto idle control.
 - increase fuel efficiency.
 - increase in compressor life.
 - reduction in noise and temperature.
 - cooler pump operation.
- ◆ Tank meets Australian Standard AS1210.
- ◆ Forklift feet on stationary units.
- ◆ Honda National Service Network.
- ◆ Warranty.
 - 3 years on pump
 - 3 years on Honda engine.
 - 5 years on tank



AFP 38



AFP 59

Dimensions (mm)	Length	Width	Height	Weight (kg)
AFP 38	940	355	820	75
AFP 49	1,100	480	850	101
AFP 49/L	1,450	470	900	114
AFP 59	1,450	470	970	155
AFP 60	1,450	470	1,000	171
AFP 70	1,500	520	1,150	208

* Dimensions exclude wheels and handle

Product Code	Displacement CFM	L/min	Free Air Delivery CFM	L/min	Motor Hp	Honda Motor	Tank Litres	Pump Model	Cylinders / Stages	Max. Pressure
AFP 38	18.3	518	14.1	400	6.5	GX200	60	B3800	2/1 Stage	130psi
AFP 49	18.0	509	14.8	419	6.5	GX200	73	B4900	2/2 Stage	160psi
AFP 49/L	18.0	509	14.8	419	6.5	GX200	155	B4900	2/2 Stage	160psi
AFP 59	23.0	651	18.4	521	9.0	GX270	155	B5900	2/2 Stage	160psi
AFP 60	29.2	826	23.3	659	13.0	GX390	155	B6000	2/2 Stage	160psi
AFP 70	42.7	1,208	34.2	968	13.0	GX390	155	B7000	2/2 Stage	160psi

* Electric start option available (battery, battery bracket and leads not included)

* Heavy Duty Anti Vibration Pads available for stationary units.

* Filter regulator not included.

CFM x 28.3 = Litres per minute

B3800 - Single stage pump.

Specifications/configuration may change at any time without notice.

For improved air quality please consider our Refrigerated Dryers and Filters.